



HEATLOK HFO PRO

DECLARATION OF PERFORMANCE

SECTION 1: Product Name

HEATLOK HFO Pro

SECTION 2: Intended use

Thermal insulation for buildings

SECTION 3: Manufacturer

ICYNENE LAPOLLA SPRL
Clos Chapelle aux Champs, 30 B-1200 BRUSSELS
BELGIUM

SECTION 4: Authorised Representative

Not relevant

SECTION 5: System of AVCP

AVCP 3

SECTION 6: Harmonized Standard

EN 14315-1:2013

Notified testing laboratory no 1020 and 1391 determined the production type under system AVCP 3

SECTION 7: Declared Performance

Characteristic	Performance	Harmonized Standard
Reaction to fire	E	EN 14315-1:2013 and EN 12667
Water permeability - short term water absorption by partial immersion	W0,157	
Thermal resistance and thermal conductivity	NPD	
Water vapour permeability	MU47	
Compressive strength or compressive stress	CS(10\Y)150	
Durability of reaction to fire against ageing / degradation	Reaction to fire does not change with time	
Durability of thermal resistance against ageing / degradation	See performance chart	
Durability of compressive strength against ageing / degradation	Compressive strength does not change with time	
Continuous glowing combustion	No harmonized test method available	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above. Signed for and on behalf of the manufacturer by:

DoP : Declaration of Performance

CPR : Construction Product Regulation

Declaration of Performance

DoP 021/01-2021



Pierre-Antoine BERTIER

EU Certification Director